



PVC Warning Tape (Premium) #PN15

DESCRIPTION

With PVC as the base material, it has good abrasion resistance and can meet the requirements of long-term use. High-viscosity glue provides strong stickiness, no glue residue. It has good fitting feature. Bright colors provide eye-catching safety warning effects.

APPLICATIONS

Commonly used for ground marking and division, such as warehouse floor planning, shopping mall floor division, etc.


PRODUCT FEATURES

- Material: PVC
- Overall Grade/Function: Economic
- Adhesive: Nature rubber
- Weight-bearing: < 10 KG
- Suitable surfaces: Suitable for smooth or rough surface

Characteristics:

- Good fitting feature
- Strong stickiness
- No glue residue
- Bright colors
- Provide eye-catching safety warning effects

COLOR(S)



Black and yellow



Red and white

CORE SIZE

3 in / 7.7cm

WIDTH(S)

48mm 50mm

LENGTH(S)

33m

Contact your ADHES sales representative for other available sizes

SPECIFICATIONS

STANDARD

Thickness	150±10um
Initial adhesion	12#
Holding power	24 hours
180° Peel Strength	3.3 N/25mm
Tensile Strength	53.5 N/25mm
Elongation	196.8%
Operating Temperature	0~40 C
Applicable Temperature	-20-60 C
Service Life	1 Year
Storage Suggestion	23°C±2 C (73°F), 50% of Relative Humidity

IN-STOCK MODEL NUMBER



■ ADU-P4833NBY15

■ ADU-P4833NRW15