TECHNICAL DATA SHEET





DESCRIPTION

The BOPP tape is made of Bio-Oriented Polypropylene, coated with acrylic adhesive or pressure-sensitive HOTMELT adhesive. With resistance to peeling, excellent adhesiveness, viscosity and stretching; light weight, friendly to the environment, easy to apply. In various colors with the option of personalized printing.

APPLICATIONS

Medium and heavy packaging in commercial . And industrial transportation Various humid conditions and extreme low-temperature environment Various surface materials.

PRODUCT FEATURES

Material: BOPP (Biaxially Oriented Polypropylene)

Overall Grade/Function: Regular

Adhesive: Natural rubber Weight-bearing: <20KG

Suitable surfaces: Mainly used for sealing boxes

Characteristics:

- Low temperature resistance
- Super sticky
- Strong holding power and strong peeling strength

COLOR(S)



CORE SIZE

3in / 7.7cm

WIDTH(S)

48mm

LENGTH(S)

50m 100m

Contact your ADHES sales representative for other available sizes

SPECIFICATIONS

Thickness	50±2um
nitial adhesion	10#
Holding power	24 hours
180° Peel Strength	14.7 N/25mn
Tensile Strength	84.4 N/25mn
Elongation	145.2%
Operating Temperature	0~40℃
Applicable Temperature	0-60℃
Service Life	1 Year

Storage Suggestion 23°C±2°C (73°F),

50% of Relative Humidity

STANDARD

IN-STOCK MODEL NUMBEI

