TECHNICAL DATA SHEET





DESCRIPTION

The BOPP tape is made of Bio-Oriented Polypropylene, coated with acrylic adhesive or pressure-sensitive HOTMELT adhesive. With resistance to peeling, excellent adhesiveness, viscosity and stretching; light weight, friendly to the environment, easy to apply. In various colors with the option of personalized printing.

APPLICATIONS

Apply at the depot, home and office use. The tape could be used for shipping, packaging, box and carton sealing, removing clothing dust and pet hair.

PRODUCT FEATURES

Material: BOPP (Biaxially Oriented Polypropylene)

Premium Overall Grade/Function:

Adhesive: Hot Melt

Weight-bearing: < 30KG

Suitable surfaces: Mainly used for sealing boxes

Characteristics:

- Excellent quick stick characteristic
- Transparent & Excellent Adhesive
- Premium

COLOR(S)



CORE SIZE

3 in / 7.7cm

WIDTH(S)

48mm 50mm

LENGTH(S)

50m 100m

Contact your ADHES sales representative for other available sizes

SPECIFICATIONS STANDARD

Thickness 50±2um Initial adhesion 22# Holding power 24 hours 180° Peel Strength 14 3 N/25mm Tensile Strength 95.7 N/25mm Elongation 147.2% 10~40°C **Operating Temperature** Applicable Temperature -5-60°C 1 Year Service Life

23°C±2 [°]C (73°F), Storage Suggestion 50% of Relative Humidity

IN-STOCK MODEL NUMBEI







■ ADU-50055TH

■ ADU-50110TH

■ ADU-B48914HT50