TECHNICAL DATA SHEET





DESCRIPTION

The BOPP tape is made of Bio-Oriented Polypropylene, coated with acrylic adhesive or pressure-sensitive HOTMELT adhesive. With resistance to peeling, excellent adhesiveness, viscosity and stretching; light weight, friendly to the environment, easy to apply. In various colors with the option of personalized printing.

APPLICATIONS

Apply at the depot, home and office use. The tape could be used for shipping, packaging, box and carton sealing, removing clothing dust and pet hair.

PRODUCT FEATURES

Material: BOPP (Biaxially Oriented Polypropylene)

Overall Grade/Function: **Heavy Duty**

Adhesive: Acrylic solvent Weight-bearing: < 30KG

Suitable surfaces: Mainly used for sealing boxes

Characteristics:

- Excellent quick stick characteristic
- Crystal transparent
- No bubbles
- No noise

COLOR(S)

Transparent

CORE SIZE

1.7in / 4.3cm 3in / 7.7cm

WIDTH(S)

48mm

LENGTH(S)

27m 50m

Contact your ADHES sales representative for other available sizes

SPECIFICATIONS

Thickness	50±2um
Initial adhesion	11#
Holding power	24 hours
180° Peel Strength	4.4 N/25mm
Tensile Strength	98.3 N/25mm
Elongation	148.7%
Operating Temperature	0~40°C
Applicable Temperature	-15-65 ℃
Service Life	1 Year

Storage Suggestion 23°C±2°C (73°F). 50% of Relative Humidity

IN-STOCK MODEL NUMBEI

- ADU-B4850SS50NN
- ADU-B4827SS50NN





STANDARD