



STRETCH FILM #60GAU

DESCRIPTION

Stretch film mainly adopts linear polyethylene (LLDPE) resin and tackifier with a certain proportion, and it is a popular packaging material. The two most common technologies are Cast and Blown. Cast is more commonly used for industries.

APPLICATIONS



It is mainly used in the collective packaging and tray packaging and also widely used in various industries such as containers (cans), chemicals, ceramics, glass, hardware machinery and equipment (stainless steel plates), paper (paper cutting), textiles, furniture, electronic product boxes.

PRODUCT FEATURES

Material: LLDPE
 Overall Grade/Function: Premium
 Adhesive: None
 Characteristics:

- High Performance
- 5-layer co-extrusion technology
- High flatness
- Good tensile strength
- Puncture resistance

COLOR(S)

 White Transparent  Bright Black

CORE SIZE

3.3in / 8.4cm

WIDTH(S)

457mm 500mm

LENGTH(S)

305m 457m

Contact your ADHES sales representative for other available sizes

SPECIFICATIONS

SPECIFICATIONS	STANDARD
Thickness	15±10%um
Tensile Strength	Longitudinal≥13.92 N/25mm Lateral≥6.23N/25mm
Elongation	Longitudinal≥596.17% Lateral≥919.47%
Operating Temperature	-5~40 C
Applicable Temperature	-20-65 C
Service Life	1 Year
Storage Suggestion	23°C±2 C (73°F), 50% of Relative Humidity

IN-STOCK MODEL NUMBER



- ADU-151000TU18
- ADU-151500TU18